




INCINER8

WWW.INCINER8.COM

INCINER8
Leader of Thermal Treatment Solutions

INCINER8 I8-PC2 TECHNICAL DATASHEET



i8-PC2 incinerator is our flagship model for pet cremation services and has been designed to incorporate features specifically for this sector. The compact design boasts a large diameter front-loading door allowing clear, unimpeded access for the operator. The high-capacity cylindrical chamber provides exceptional combustion and is suitable for both communal cremations and the cremation of large-breed pets individually. Advanced control systems regulate a steady air supply to the chamber ensuring optimum fuel and efficiency.



LOAD CAPACITY

Inciner8 uses four main size guides within our comprehensive range to differentiate our models, from S to XL. This allows us to provide you with a machine that perfectly fits your needs and your waste stream.



CORETEX INSULATION

Coretex insulation - Triple insulation Coretex technology uses a combination of high-density insulation board, custom refractory concrete and thick steel to deliver the ultimate incineration insulation.



FRONT LOAD

Front-loading increases accessibility and ease of use for manual handling and is ideal for the medical and pet cremation sectors. It allows ash to be easily and carefully removed and makes the overall accessibility into the primary chamber easier for the operator.



CONTAINER CONFIGURE

Certain Incinerators have the capability to be configured into mobile containerised incineration units. This gives them the benefit of being easy to lock up and secure when at a remote site, as well as being easier to move with added benefits of minimal setup and dismantling time.



USB DATA LOGGING

The optional USB data logging allows the operator to digitally download all data from the incinerator and export them into easy to read formats to share with relevant authorities. This allows you to comply with local laws with ease and gives you the capability to log all your data on a small and secure device.

Designed and manufactured in Britain to ISO 9001 accredited quality assurance standards. Our pet cremation systems have been ergonomically designed with a large front loading door and chamber, making it easy to load and remove ashes.



i8-PC2 FEATURES

- Cladded for heat retention, cool touch & hygiene control
- Patented safety handle for easy access to chamber
- High quality refractory lining and insulation
- Easy to use CE2 control panel
- Programmable temperature control for complete combustion
- Temperature monitoring
- Secondary chamber* with 2 second retention time
- Quick & easy start up
- Low energy consumption levels



* Our primary and secondary combustion chambers are constructed from superior grade steel and state-of-the-art monolithic concrete refractory with a unique concave design to prevent cold spots and maximize heat retention during the start-up and combustion processes. When the secondary burner is activated a flame curtain is created which ensures the thermal decomposition of smoke and harmful emissions to produce a clean, odourless vapour exiting the chimney stack.

TECHNICAL BREAKDOWN

model: **I8-PC2**

HT THERMOCOUPLES

Independent control of primary and secondary temperatures via the control panel.

SECONDARY CHAMBER

Retains and re-burns the exhaust gases for minimum of 2 seconds at 850°C.

CHIMNEY STACK

Stainless steel stack for longevity. Fitted with a Velocity Cowl as standard.

PRIMARY CHAMBER

Chamber designed for maximum air flow and circulation which in turn improves efficiency and total burn time.

SAFE USE HANDLES

Easy to open and close loading door. Designed to increase operator safety.

COOL TOUCH CLADDING

Steel cladding to reduce risk of infection and increase longevity of system.

ECOFLAM BURNERS

These are some of the cleanest, most efficient burners available, and can be supplied as gas or oil fired.



Photos are for illustration purposes only. Specification (including paint colours) are subject to change without notice and do not affect the performance of the machine.

HOW INCINERATION WORKS

Incineration is a waste treatment process which utilises the combustion of organic substances contained within materials to convert waste into ash, heat and flue gas. The ash residue is mostly formed by inorganic constituents of the waste which may take the form of solid lumps or powder.

Heat produced by the incineration process can be fed into a heat exchanger to produce hot water or air which can be used for cleaning or heating purposes. The remaining flue gases are passed through pollution control devices in the form of a secondary combustion chamber or additional filtration (if required) and then expelled to atmosphere.

APPLICATIONS

Our pet cremation incinerators have been designed to help start-up pet cremation businesses or for more established businesses that are looking to improve their existing incinerators with more efficient and ergonomic models. Our systems are suitable for a wide range of animals such as:

- Dogs
- Cats
- Hamsters
- Rabbits
- Birds
- Reptiles



For additional information, or to speak to one of our expert team:

Call
+44 (0) 1704 884020

Email
sales@inciner8.com

 **INCINER8**
www.inciner8.com

TECHNICAL SPECIFICATION

model: **I8-PC2**

OPERATIONAL SPEC		PHYSICAL SPEC	
Combustion Chamber Volume (m ³)	0.57m ³	Assembled L/W/H (mm)	2400 x 1350 x 3840
Burn Rate (Kg p/h)	Up to 50Kg	Assembled Weight (Kg)	2700kg
Fuel Consumption (Ltrs p/hour)	15-20 ltrs	Door Size (mm)	0.57Ø
Time To Temp	45-60 mins	Thermocouples (Qty)	2
Gas retention Time (Seconds)	2 secs	Steel Thickness (mm)	3mm
Loading Method	Front Load	No. Of Burners	2
Fuel Options	Light Oil or Gas/LPG	Refractory Composition	Coretex
Electricity Supply	110v or 230v	Operating Footprint	23.49m ²
Control Panel (IP Rating)	IP54	Cool Touch Cladding	Yes
Heat Recovery	No	Viewing Portal	No
Auto Ash Removal	No	Tertiary Air Fan	Yes
Auto Loader Compatible	No		
Remote Monitoring	No		
Ash Residue	3-5%		
Recommended Operational Temperature	850°C		

*The above figures are guidelines ONLY.

Ecoflam burners are renowned worldwide for providing high efficiency and reliable operation with significant energy savings and feature extreme ease of installation, maintenance and flexible boiler-burner matching. This model is fitted with low NOx burners as standard to ensure a complete and clean burn cycle, this reduces installation time and maintenance.

ECOFLAM BURNER SPECIFICATIONS

PARAMETER (1/2 HR AV)	LIMITS	MEASURED*
Total Dust	30mg/m ³	12mg/m ³
Sulphur Dioxide	200mg/m ³	2.4mg/m ³
Nitrogen Dioxide	400mg/m ³	60mg/m ³
Carbon Monoxide	100mg/m ³	78.3mg/m ³

*The above figures are guidelines ONLY.

Ecoflam

- MAX 1-12 have electrical frequency 50-60 Hz
- High efficiency fan ventilation system (HPV)
- Low NOx version class 3 with yellow flame
- Designed in compliance with current regulations
- ISO 9001 and VISION 2000 certification
- All burners are fire tested



NB: picture for illustration purposes only

AVERAGE EMISSIONS / EU STANDARDS

All of our secondary combustion chambers are designed to operate at 850 - 1200°C to re-burn waste gases which prevents smoke, odours and harmful emissions. Dioxins and similar gaseous components are destroyed by a combination of homogeneous high temperatures, excess oxygen levels and sufficient gas residence time in the secondary chamber which our incinerators achieve.

Emissions are largely a product of the waste materials therefore care should be taken when selecting the most appropriate method of pollution control to ensure compliance with your local emissions standards, please discuss this with our sales team if you aren't sure.

CALL INCINER8 AND START BUILDING SOLUTIONS TO YOUR WASTE CHALLENGES TODAY!

**+44 (0) 1704 884020 OR
EMAIL SALES@INCINER8.COM**

For additional information, or to speak to one of our expert team:

Call
+44 (0) 1704 884020

Email
sales@inciner8.com

INCINER8
www.inciner8.com